





BUILT AFRICA TOUGH Designed and Manufactured in South Africa



Axles

Desmond Axle (4x2) Front Graziano PR 24 axle Rear

Steering

- Articulated with 40° steering angle either side
- Load-sensing, orbital-controlled
- Ground driven emergency steering

Tyres

Front/Rear: 26.5 x R25 Radial

Frame

Heavy duty robust frame, front and rear with tube type oscillation, adjustable.

Electrics

Voltage 24 Volt

2 x 12 Volt sealed type Battery Alternator: 24 Volt / 70 Amp

Brakes

Air-operated S-cam failsafe drum brakes Front 2 wheels

Rear 2 wheels Air over hydraulic disc brakes

Park Brake Air-operated failsafe disc brake on propshaft

and front axle

Cab Features

- ROPs and FOPs certified
- Rubber mounted
- Fully adjustable suspension seat with seat belt
- Trainer driver seat
- Air conditioner and tinted windows
- Orange beacon light and rear work lights
- Dashboard with full instrumentation
- Interior dome light
- Windscreen wiper

Pneumatic System

Capacity 80 Liters

Working pressure 120 Psi (8.1 Bar) with dual circuit unloader

valve controlled system

Engine

Type

Model QSB 260 - TIER 3. Turbocharged & intercooled

Capacity

194kW @ 2200 RPM Power Torque 990 Nm @ 1500 RPM

Loadbin Volume

SAE 1:1 16.20m³ SAE 2:1 13,30m³ STRUCK 10.00m³





PORT SHEPSTONE HEAD OFFICE

PO Box 111 Port Shepstone 4240, South Africa

Web: www.dezzi.co.za

Transmission

Type

Gears

6WG210 Model

Constant mesh counter shaft with integral Gearing

drop box. Forward - 6

Reverse - 3 Speed 50Km/H

Torque Converter Single phase 3 element, lock-up clutches

effective in all gears. Downshift protection.

Hydraulic System

Oil Capacity 170 Liters

Fixed displacement external gear pump **Pumps**

- 17 Mpa - 5 Mpa Steering Working Pressure

Tipping Full flow filtration

Service Capacities

Cooling system 50 Litres Engine Crankcase 21 Litres Rear Axle Differential 40 Litres Transmission 18 Litres Diesel Tank 200 Litres

Standard Equipment

Emergency braking

Full road ordinance lights

Front tow hooks

Hinged belly plate under engine

Air cleaner service indicator

Rear window guard

Back-up alarm

Wheel mud flaps

Optional Equipment


- Radio/Tape
- Tachograph
- Bin Liner kit
- Engine monitoring system
- Light guards

Operational Weights

		Tare	Gross	Payload
Front Axle	:	9480	18980	9500
Rear Axle	:	7420	22920	15500
TOTAL	:	16900	41900	25000

Tipping Times (Approx.)

9.8 Seconds Up Down 7.1 Seconds



Dimensions are approximate